



GENERAL NOTES

1. VALVE SHALL BE IRON BODY, CLASS 125, FLANGED ENDS, HYDRAULICALLY OPERATED, PILOT CONTROLLED, DIAPHRAGM TYPE, GLOVE PATTERNED VALVE. IT SHALL BE TREATED AT 175 P.S.I. MINIMUM PRESSURE.
2. MANUFACTURERS NAME, YEAR OF MANUFACTURE, SIZE OF VALVE AND GUARANTEED WORKING PRESSURE SHALL BE ENGRAVED ON THE VALVE OR AN A NAMEPLATE ATTACHED TO THE VALVE.
3. VALVE SHALL BE OPERATED BY A CONTROL SYSTEM WHICH INCLUDES PILOT CONTROLS FOR PRESSURE REDUCING AND FOR SUSTAINING. BOTH PILOT CONTROLS SHALL BE FIELD ADJUSTABLE FOR ANY PRESSURE IN THE RANGE OF 50 TO 120 P.S.I.

DETAIL NO.
G-3323

**CITY OF GOODYEAR
STANDARD DETAIL**

APPROVED BY:
Goodyear Standards and
Policies Committee
7/97

PRESSURE REDUCING & SUSTAINING VALVE

DETAIL NO.
G-3323